GHIBLI AW: Robust and ergonomic.

The GHIBLI AW is the robust and ergonomic heat gun used for shrink in cable manufacturing, heating and forming in the automobile industry, lap welding of truck sheeting and for deburring plastic parts. Thanks to the easy-to-grip, two-component frame, the GHIBLI AW fits perfectly in the hand. Temperature and air volume can easily be adjusted with the proven and intuitive "e-Drive" operating unit. The stand that is included in the scope of delivery and the

GHIBLI AW Thanks to the included stand, the GHIBLI AW can be placed in an optimum position at the workstation, thus reducing fatigue. 2 2 Practical air filter Regular cleaning of the air filters ensures optimum air flow and 3 maximum power. 4 3 Leister e-Drive Temperature and air volume are easy to control and inspect with the proven "e-Drive" operating unit for reproducible results. Fatique-free working Thanks to the integrated suspension lug, the GHIBLI AW can be suspended for fatigue-free work. 5 All of its predecessor's nozzles also fit on the GHIBLI AW. Comprehensive selection of compatible accessories. 6 **Ergonomic handling** The two-component handle and the perfect device balance ensure an optimal **Swiss** grip and comfortable work, even under the harshest of conditions. made

Heat gun

practical device suspension make working easier. The air filters can be readily removed and cleaned. And of course, all of the nozzles from its predecessor fit the new GHIBLI AW.



Shrink applications in cable manufacturing – ideal with the GHIBLI AW

Heat gun

GHIBLI AW

- Ergonomic heat gun
- Digital temperature control
- Five-stage air volume control
- "e-Drive" operating unit for optimum process control
- 100% Swiss Made

Technical data		
Voltage	V~	230 / 120
Frequency	Hz	50 / 60
Power	W	2300 / 1800
Temperature	°C	65 – 620
Air volume	I/min	140 – 270
Ø Nozzle holder	mm	36.5
Emission	dB(A)	67
Dimensions (L \times W \times H)	mm	$280 \times 220 \times 90$
\varnothing Handle	mm	45
Weight	kg	1.18
Conformity mark		C€
Approval mark		\$
Protection class II		

Article No.:

148.061	GHIBLI AW, 230 V / 2300 W, Euro plug
150.168	GHIBLI AW, 230 V / 2300 W, UK plug
150.169	GHIBLI AW, 230 V / 2300 W, CH plug
150.170	GHIBLI AW, 120 V / 1800 W, CEE plug
148.079	GHIBLI AW, 100 V / 1500 W, JP plug

Scope of delivery: GHIBLI AW, case, stand, Operating Instructions

Accessories for GHIBLI AW

106.998	Wide slot nozzle 20 mm, push-fit
106.999	Wide slot nozzle 40 mm, push-fit
107.154	Tubular nozzle Ø 5 mm, push-fit
107.006	Extension nozzle ∅ 5 × 130 mm, straight
107.308	Sieve reflector $50 \times 35 \text{ mm}$
107.309	Sieve reflector $35 \times 20 \text{ mm}$
107.313	Spoon reflector 25×30 mm, with screw connector
107.325	Solder reflector 17 \times 34 mm, push-fit
107.319	Sieve reflector Ø 65 mm
107.345	Welding mirror 135 mm, push-fit
107.007	Ø 37 mm Dehorning nozzle
106.132	45×250 mm Shell reflector, push-fit
145.582 145.580	Heating element, 230 V / 2200 W Heating element, 120 V / 1700 W

General accessories ≥ 32/33 🛄



